

## Long Shank Dynamo Eyebolts

### metric coarse & BSW thread

**Material:** High tensile steel  
**Safety Factor:** MBL equals 5 x SWL  
**Finish:** Self colour  
**Certificate:** This product is supplied with an EC declaration of conformity  
**Note:** Electro galvanised (zinc plated) also available - prices on request  
**Special Note:** These eyebolts are for a vertical lift only

#### Metric thread

safe working load	diameter thread	diameter eye inside	diameter eye	length base to centre	length thread	base height	diameter base	product code	weight each
tonnes	a mm	b mm	c mm	d mm	e mm	f mm	g mm		kg
0.15	8	22	9.5	27	100	6	19	EBDML08	0.11
0.25	10	22	9.5	27	100	6	19	EBDML10	0.12
0.32	12	29	11	35	100	8	25	EBDML12	0.17
0.63	16	32	13	41	114	9.5	29	EBDML16	0.35
1.25	20	41	16	54	127	11	35	EBDML20	0.60
2.00	24	51	19	64	127	13	41	EBDML24	1.10

#### BSW thread

safe working load	diameter thread	diameter eye inside	diameter eye	length base to centre	length thread	base height	diameter base	product code	weight each
tonnes	a inch	b inch	c inch	d inch	e inch	f inch	g inch		kg
0.25	3/8	7/8	3/8	1.1/16	4	1/4	3/4	EBDWL10	0.09
0.50	1/2	1.1/16	7/16	1.3/8	4	5/16	1	EBDWL13	0.14
0.80	5/8	1.1/4	1/2	1.5/8	4.1/2	3/8	1.1/8	EBDWL16	0.24
1.20	3/4	1.9/16	11/16	2.1/8	5	1/2	1.7/16	EBDWL19	0.43
2.20	1	2	13/16	2.7/16	5	1/2	1.5/8	EBDWL25	0.88

## Green Pin® Eyebolts

### metric coarse thread, generally to DIN 580

**Material:** Carbon steel, C15  
**Safety Factor:** MBL equals 4 x SWL  
**Standard:** Generally to DIN 580  
**Finish:** Self colour  
**Certificate:** This product is supplied with an EC declaration of conformity

working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	height	product code	weight per 100 pcs
tonnes	a mm	b mm	c mm	d mm	e mm	f mm	g mm		kg
0.07	6	20	36	20	13	6	36	EBGMS6	6.00
0.14	8	20	36	20	13	6	36	EBGMS8	6.00
0.23	10	25	45	25	17	8	45	EBGMS10	10.30
0.34	12	30	54	30	20.5	10	53	EBGMS12	17.70
0.49	14	35	63	35	27	12	60	EBGMS14	27.70
0.70	16	35	63	35	27	12	62	EBGMS16	28.00
0.90	18	40	72	40	30	14	71	EBGMS18	40.50
1.20	20	40	72	40	30	14	71	EBGMS20	42.40
1.50	22	45	81	45	35	14	80	EBGMS22	67.30
1.80	24	50	90	50	36	18	90	EBGMS24	83.40
2.50	27	50	90	50	36	18	90	EBGMS27	122.00
3.20	30	65	108	60	45	22	109	EBGMS30	166.00
4.30	33	65	108	60	45	22	110	EBGMS33	216.00
4.60	36	75	126	70	54	26	128	EBGMS36	265.00
6.10	39	75	126	70	54	26	130	EBGMS39	334.00
6.30	42	85	144	80	63	30	147	EBGMS42	403.00
8.00	45	85	144	80	63	30	150	EBGMS45	521.00
8.60	48	100	166	90	68	35	168	EBGMS48	632.00
11.50	56	110	184	100	78	38	187	EBGMS56	880.00
16.00	64	120	206	110	90	42	208	EBGMS64	1240.00

sizes marked \* are additional and proportional to the specification