

## EyenuTs

### metric coarse & BSW thread

**Material:** High tensile steel  
**Safety Factor:** MBL equals 5 x SWL  
**Finish:** Self colour (Electro galvanised (zinc plated) also available)  
**Certificate:** This product is supplied with an EC declaration of conformity

#### metric coarse thread

safe working load	diameter thread	diameter eye	diameter base	diameter eye inside	base height	height overall	product code	weight each
tonnes	a mm	b mm	c mm	d mm	e mm	f mm		kg
0.30	10	13	29	44	22	78	ENCMS10	0.25
0.50	12	13	29	44	22	78	ENCMS12	0.26
0.80	16	13	29	44	22	78	ENCMS16	0.27
1.20	20	16	39	49	26	84	ENCMS20	0.45
2.20	24	19	44	52	38	111	ENCMS24	0.79

#### BSW thread

safe working load	diameter thread	diameter eye	diameter base	diameter eye inside	base height	height overall	product code	weight each
cwts	a inch	b mm	c mm	d mm	e mm	f mm		kg
5	3/8	13	29	44	22	78	ENCWS10	0.24
10	1/2	13	29	44	22	78	ENCWS13	0.26
16	5/8	13	29	44	22	78	ENCWS16	0.26
24	3/4	16	39	49	26	84	ENCWS19	0.45
32	7/8	16	39	49	26	84	ENCWS22	0.45
44	1	19	44	52	38	111	ENCWS25	0.79

## Bownuts

### metric coarse & BSW thread

**Material:** High tensile steel  
**Safety Factor:** MBL equals 5 x SWL  
**Standard:** Generally to B.S. 3974 - Part 1 - 1974  
**Finish:** Self colour (Electro galvanised (zinc plated) also available)  
**Certificate:** This product is supplied with an EC declaration of conformity

#### metric coarse thread

safe working load	diameter thread	diameter eye	diameter base	diameter eye inside	base height	height overall	product code	weight each
tonnes	a mm	b mm	c mm	d mm	e mm	f mm		kg
0.23	8	10	32	25	16	64	BNCMS08	0.15
0.36	10	10	32	25	16	64	BNCMS10	0.15
0.53	12	12	38	30	17	73	BNCMS12	0.27
1.01	16	12	38	30	17	73	BNCMS16	0.29
1.58	20	14	45	40	25	102	BNCMS20	0.50
2.28	24	17	50	50	29	124	BNCMS24	0.90
3.65	30	26	70	75	29	149	BNCMS30	2.20
5.34	36	26	70	75	29	149	BNCMS36	2.20

#### BSW thread

safe working load	diameter thread	diameter eye	diameter base	diameter eye inside	base height	height overall	product code	weight each
tonnes	a inch	b mm	c mm	d mm	e mm	f mm		kg
0.25	3/8	10	32	25	16	64	BNCWS08	0.15
0.50	1/2	12	38	30	17	73	BNCWS12	0.27
0.80	5/8	12	38	30	17	73	BNCWS16	0.27
1.20	3/4	14	45	40	25	102	BNCWS19	0.58
1.60	7/8	14	45	40	25	102	BNCWS22	0.58
2.20	1	17	50	50	29	124	BNCWS25	0.90
3.50	1.1/4	26	70	75	29	149	BNCWS30	2.20
4.75	1.1/2	26	70	75	29	149	BNCWS36	2.20